

WARCO® BILTRITE® PRODUCT COMPARISON

WARCO® BILTRITE®

West American Rubber Company, LLC Biltrite Ripley Operations, LLC

America's choice for quality rubber.™



West American Rubber Company, LLC



Biltrite Ripley Operations, LLC

	1300 Series	Style #10
Durometer:	40-50-60-70-[80]	40-50-60-70-80
Specifications:	Not Listed	1BC408-810
Thickness:	1/32" to 1/2" (1/2" to 3" Heavy Gage Thickness)	1/32" to 2"
Widths:	36" – 48"	36" – 48" 72"
Heavy Gage Lengths:	12 Ft. – 16.5 Ft.	30 Ft. – 60 Ft.

	PSA Ready Series	Style #12 Matte Finish
Durometer:	40-50-60-70-80	50-60-70-80
Specifications:	Not Listed	1BC508 to 810
Thickness:	1/32" to 1/4"	1/16" to 1/4"
Widths:	36" or 48"	36" to 72"

	5100 Series	Style #15
	51% Neoprene	50% Neoprene
Durometer:	30-40-50-60-70-80	50-60-70-80
Specifications:	MIBC507 etc. [1000PSI]	1BC515 etc. [1500 PSI]
Thickness:	1/64" thru 1/2"	1/16" thru 1"
Widths:	36" [48"- Some sizes Stock]	36" Stk. – 48" Non Stock



West American Rubber Company, LLC

Sales, Manufacturing and Distribution

TEL (714) 532-3355 • FAX (714) 532-2238

1413 Braden Court • Orange, California 92868

WWW.WARCO.COM



Biltrite Ripley Operations, LLC

Sales, Manufacturing and Distribution

TEL (800) 245-8748 • FAX (662) 837-0132

16310 Highway 15 North P.O. Box 577

Ripley, Mississippi 38663

America's choice for quality rubber.™



West American Rubber Company, LLC



Biltrite Ripley Operations, LLC

	Commercial Nitrile	Style #35
	Economy and Special Grade Nitrile	Commercial Grade Nitrile
Durometer:	40-50-60-70-80	40-50-60-70 [80 N/S]
Specifications:	Not Listed	1BF408-810
Gages:	1/32" thru 1/4"	1/32" thru 1"
Thickness:	Econ. 36" – Spec 36" and some 48"	36" and 48"

	High Grade Nitrile	Style #36
	High Grade Nitrile	Premium Grade Nitrile
Durometer:	40-50-60-70-80-90	60
Specifications:	M1BG 610,710,810	5BG613A14,B13 E014,E034F17
Gages:	1/16" thru 1/4"	1/16" thru 1/4" [Stock]
Thickness:	36" [48" 1 Size]	36"

	WARCO White®	Style #37 - WHITE
Durometer:	45-55-65-80	60
Specifications:	M1BG 607	Yes – But none listed.
Gages:	1/16" thru 1/4"	1/16" thru 1/4"
Thickness:	36" – [Some 48" 1/8" and 1/4"]	36" and 48"



West American Rubber Company, LLC

Sales, Manufacturing and Distribution

TEL (714) 532-3355 • FAX (714) 532-2238

1413 Braden Court • Orange, California 92868

WWW.WARCO.COM



Biltrite Ripley Operations, LLC

Sales, Manufacturing and Distribution

TEL (800) 245-8748 • FAX (662) 837-0132

16310 Highway 15 North P.O. Box 577

Ripley, Mississippi 38663

America's choice for quality rubber.™



West American Rubber Company, LLC



Biltrite Ripley Operations, LLC

	Economy Grade EPDM	Style #40
	Economy Grade EPDM	Commercial Grade EPDM
Durometer:	50-60-70	40 [N/A] 50-60-70-80
Specifications:	Not Listed	3BA408C12 to 808
Thickness:	1/64" thru 1/4"	1/16" thru 1/4"
Widths:	Econ. 36" and [48" - some sizes]	36" and 48"

	High Grade EPDM	Style #45
	High Grade EPDM	High Grade EPDM
Durometer:	40-50-60-70-80	50-60-70-80
Specifications:	M1BA 407 to 810	3BA515A14,B13,C12,F17
Thickness:	1/64" thru 1/4"	1/16" thru 1/4"
Widths:	36" – (48"- 3 sizes)	36" – [48"available on request]

	Pure Gum Floating	Style #28 - Natural Rubber
	Floating FDA Approved	Floating and FDA Approved
Durometer:	40	40
Specifications:	M1AA417 [2700 PSI]	1AA430 [3000 PSI]
Gages:	1/64" thru 1/2"	1/32" thru 1"
Thickness:	36" Primarily	36" – 48" [72" on request]



West American Rubber Company, LLC

Sales, Manufacturing and Distribution

TEL (714) 532-3355 • FAX (714) 532-2238

1413 Braden Court • Orange, California 92868

WWW.WARCO.COM



Biltrite Ripley Operations, LLC

Sales, Manufacturing and Distribution

TEL (800) 245-8748 • FAX (662) 837-0132

16310 Highway 15 North P.O. Box 577

Ripley, Mississippi 38663

America's choice for quality rubber.™



West American Rubber Company, LLC



Biltrite Ripley Operations, LLC

	SBR Calendered Sheet [SBR – Black]	Style #20 Red
Durometer:	40-50-60-70-80	75
Specifications:	Not Listed	Yes ASTM D 1330 GR2 [400PSI]
Thickness:	1/32" thru 1/4"	1/16" thru 1/4"
Widths:	36", 48" & 55"	36" – 48" & 72"
Finishes:	Smooth, Fabric also available	Smooth or Fabric

	Neoprene Calendered Cloth Inserted Sheet	Style #51 Neoprene Cloth Inserted
Fabric:	4 oz. Polyester or 100% 3222 count Cotton	Fabric 4 oz. Polyester only
Durometer:	70	70
Specifications:	Not Listed	Not Listed
Thickness:	1/16" thru 1/4"	1/16" thru 1/4"
Widths:	36" 48" Poly 1/16" & 1/8" 48" Cotton 1/16", 1/8" 1/4"	48"



West American Rubber Company, LLC

Sales, Manufacturing and Distribution

TEL (714) 532-3355 • FAX (714) 532-2238

1413 Braden Court • Orange, California 92868

WWW.WARCO.COM



Biltrite Ripley Operations, LLC

Sales, Manufacturing and Distribution

TEL (800) 245-8748 • FAX (662) 837-0132

16310 Highway 15 North P.O. Box 577

Ripley, Mississippi 38663

America's choice for quality rubber.™

WARCO®

West American Rubber Company, LLC

BILTRITE®

Biltrite Ripley Operations, LLC

	SBR	Style #21
	Spec Grade SBR [Red and Black]	Premium SBR [Black]
Durometer:	75	75
Specifications:	M1AA703 [435 PSI]	1330 Grade I [700 PSI]
Gages:	1/64" thru 1/4"	1/16" thru 1/4" [Available up to 1"]
Thickness:	36"	36"

	Neoprene AASHTO	Style #71
	Unsupported Clendered Sheet	Unsupported Clendered Sheet
Durometer:	50-60-70	50-60-70
Specifications:	Yes	Yes
Gages:	1/8" thru 1/2"	1/8" thru 1"
Thickness:	36" or 48"	48"

WARCO®

West American Rubber Company, LLC

Sales, Manufacturing and Distribution

TEL (714) 532-3355 • FAX (714) 532-2238

1413 Braden Court • Orange, California 92868

WWW.WARCO.COM

BILTRITE®

Biltrite Ripley Operations, LLC

Sales, Manufacturing and Distribution

TEL (800) 245-8748 • FAX (662) 837-0132

16310 Highway 15 North P.O. Box 577

Ripley, Mississippi 38663

America's choice for quality rubber.™